PHILIPPINE NATIONAL STANDARD

PNS/BAFS 311:2021 ICS 65.040.20

Slaughterhouse Equipment – Large Ruminant Restrainer – Methods of Test



BUREAU OF AGRICULTURE AND FISHERIES STANDARDS

BPI Compound Visayas Avenue, Diliman, Quezon City 1101 Philippines Trunkline: (632) 928-8741 to 64 loc. 3301-3319 E-mail: info.dabafs@gmail.com Website: www.bafs.da.gov.ph

Foreword

In 2017, the Bureau of Agriculture and Fisheries Standards (BAFS) initiated the amendment of the Philippine Agricultural Engineering Standard (PAES) on Slaughterhouse Equipment – Stunning Box/Knocking Pen – Methods of Test (PAES 514:2008) upon the endorsement of the PAES Task Force. A Technical Working Group (TWG) was created through Special Order (SO) No. 487, series of 2017 (Creation of the TWG for the development of Philippine National Standard (PNS) for Cattle Restrainer and for the revision of PAES for Slaughterhouse and Lairage), SO No. 322, series of 2019 (Creation of Technical Committee [TC] and TWG for the development of PNS for Agriculture and Fishery Products and Machinery, Tools, and Equipment), and SO No. 280, series of 2021 (Creation of TWG for the Development of PNS for Agriculture and Fishery Products, Machinery, and Equipment). This TWG was composed of representatives from relevant government agencies, academe, and private sector. The revised PAES, which is now a BAFS PNS, aimed to provide guidance to national and local authorities, engineers, technical personnel, traders, manufacturers, processors, and other relevant stakeholders on the restrainer design for the slaughterhouse of large ruminants intended for human consumption. The final draft standard was reviewed and finalized through a series of stakeholder consultations and TWG meetings conducted via online platforms.

This PNS/BAFS includes the following significant changes compared to the previous PAES:

- 1. Replacement of the term "Stunning Box/Knocking Pen" to "Large Ruminant Restrainer";
- 2. Amendment of the scope to specify restrainers installed in slaughterhouse;
- 3. Limitation of the scope for large ruminants to cover carabao and cattle only;
- Inclusion of the Code of Good Animal Husbandry Practice for Beef Cattle and Carabao (PNS/BAFS 200:2017), and Republic Act No. 10631 (Animal Welfare Act of 1998) as normative references of the standard;
- 5. Inclusion of provisions for the General Condition for Test Inspection and the Role of Test Engineers;
- 6. Deletion of the numerical value for weight of the test material;
- 7. Alignment of the capacity of the restrainer with the design of the manufacturer;
- 8. Decrease on the minimum number of trials in testing the restrainer from three (3) to two (2);
- Alignment of the standard with existing valid format of Test Reports and Data Sheets used by the Agricultural Machinery Testing and Evaluation Center (AMTEC);
- 10. Decrease on the maximum capacity of required weighing scale from 1000 kg to 700 kg;
- 11. Deletion of the digital timer and protractor as recommended instruments in Annex A;
- 12. Inclusion of other notable observations (e.g., presence of safety features/locks, vocalization, etc.) on the restrainer and ruminant during testing in Annex C; and
- 13. Deletion of Annex D Performance after Test Data Sheet.

This standard cancels and replaces the PAES 514:2008 Slaughterhouse Equipment – Stunning Box/ Knocking Pen – Methods of Test.

This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2.

Content

For	eword	i
1	Scope	. 1
2	Normative References	. 1
3	Terms and Definitions	. 2
4	General Conditions for Test and Inspection	. 2
5	Test Preparation	. 3
6	Pre-test observation	. 4
7	Performance test	. 4
8	Presentation of results	. 5
9	Test Report	. 5
	nex A	
Anr	nex B	. 8
Anr	nex C1	11
Bib	liography	14

1	1	Scope
2 3 4 5		standard specifies the methods of test and inspection for restrainer for large inants. Specifically, it shall be used to:
6 7 8	1.1	verify the mechanism, dimensions, materials, and accessories of the restrainer, and the list of specifications submitted by the manufacturer;
9 10	1.2	determine the performance of the equipment;
11 12	1.3	evaluate the safety features of the equipment; and
13 14	1.4	report the result of the tests.
15 16	2	Normative References
17 18 19 20 21	cont cited	following documents are referred to in the text in such a way that some or all their ent constitutes requirements of this document. For dated references, only the edition d applies. For undated references, the latest edition of the referenced document uding any amendments) applies.
22 23 24 25	(201	eau of Agriculture and Fisheries Standards – Department of Agriculture (BAFS-DA). 7). Code of good animal husbandry practice for beef cattle and carabao. (PNS/BAFS 2017)
26 27 28 29 30	306	S-DA. (2020). Agricultural structures – Slaughterhouse – Ruminants. (PNS BAFS 2020) //bafs.da.gov.ph/bafs_admin/admin_page/pns_file/BPS%20End_SLH_Ruminants.p
31 32 33		S-DA. (2021). Slaughterhouse equipment – Large ruminant restrainer – cifications. (PNS/BAFS XXX:2021)
33 34 35 36 37 38 39 40 41 42	<i>No.</i> 106	ublic of the Philippines. (2013). <i>An act amending certain sections of Republic Act</i> 8485, otherwise known as "The Animal Welfare Act of 1998" (Republic Act No. 31). s://www.officialgazette.gov.ph/downloads/2013/10oct/20131003-RA-10631-BSA.pdf

3 **Terms and Definitions** 43 44 45 For this standard, the following terms and definitions apply. 46 47 3.1 live weight 48 49 weight of ruminant prior to slaughter 50 3.2 51 52 overall height

53 distance between the horizontal supporting plane surface and the horizontal plane 54 touching the uppermost part of the restrainer

55 56 **3.3**

57 overall length

- 58 distance between the vertical planes perpendicular to the median plane of the restrainer,
- 59 each plane touching the front and rear extremities of the restrainer
- 60 61 3

61 **3.4**62 overall width

- distance between the vertical planes parallel to the median plane of the restrainer, each
- 64 plane touching the outermost point of the machine on its left and right sides
- 65

66 **3.5**

67 vocalization

- ruminant sound such as bellowing in cattle
- 69 70 **3.6**

71 test applicant

- 72 manufacturer, fabricator, inventor, direct importer, legitimate distributor, dealer, or end-73 user of the machine that officially applied for a test
- 73 74

General Conditions for Test and Inspection General Conditions for Test and Inspection

77 4.1 Role of the test applicant

78

The test applicant shall submit the specifications and other relevant information for the restrainer. They shall abide with the terms and conditions set forth by the official testing agency, provide test animals, and shoulder other variable cost to carry out the test.

- 82
- 83
- 84
- 85

86 87

4.2 Role of the representative of the test applicant

An officially designated representative of the test applicant shall be skilled and shall be able to operate, demonstrate, adjust, repair as the case maybe, and decide on matters related to the operation of the restrainer.

91

92 **4.3** Role of the test engineer

93

94 The certified test engineer shall lead the conduct of the performance testing in 95 accordance with the provisions of this standard. Furthermore, the test engineer shall 96 oversee other relevant activities prior to and after the conduct of the testing. 97

98 **4.4 Test site conditions**

99

100 The restrainer shall be tested as installed in the slaughterhouse. The site should have 101 ample provisions for animal handling, temporary storage, and workspace conforming to 102 PAES 306:2020 Agricultural Structures – Slaughterhouse for Ruminants.

103

104 **4.5 Suspension/Termination of test**105

If during the test run and the restrainer encounters major breakdown or malfunction that
will affect the performance of the machine, the test may be suspended. If the restrainer
will not be able to continue operation, the test shall be terminated.

110 **5 Test Preparation**

111

112 **5.1** Preparation of the large ruminant restrainer for testing

113

The representative of the test applicant and testing agency shall check the restrainer to ensure that it has been assembled and installed in accordance with the instruction of the manufacturer. The official testing agency shall test the restrainer in accordance with the performance requirements in PNS/BAFS XXX:2021 Slaughterhouse Equipment – Large Ruminant Restrainer – Specifications.

119

120 5.2 Test instruments

121

The suggested list of minimum test instruments needed to carry out the restrainer test is shown in Annex A. These instruments shall be calibrated regularly. It shall be physically checked and cleaned for operation before and after each tests. A checklist of instruments and materials to be used before arrival to and departure from the testing area shall be prepared.

- 127
- 128
- 129

130 **5.3 Test Animals**

131

The large ruminant to be used for testing shall be at least two (2) heads, each with a live
weight depending on the capacity of the restrainer as specified by the manufacturer.
However, if the test animals are not conforming to the recommended quantity and
characteristics relevant to the restrainer, the test engineer shall not pursue the test.

136 137

6 Pre-test observation

138

6.1 Verification of specifications

140

The specifications claimed by the manufacturer and the physical details given in Annex B shall be verified by the official testing agency. A stable and level surface shall be used as reference plane for verification of dimensional machine specifications when fully assembled and ready for use. The safety features of the restrainer shall be recorded.

145

146 6.2 Condition of the Test Animals147

The parameters listed in Item C.1 of Annex C shall be obtained and recorded before the
test operation.

- 151 **7** Performance test
- 152

153 **7.1** Operation of the restrainer

154

155 The restrainer shall be tested by performing actual and proper restraining and stunning 156 of the test animal in accordance with the Republic Act 10631 (Animal Welfare Act of 1998) 157 and the PNS Code of Good Animal Husbandry Practice for Beef Cattle and Carabao 158 (PNS/BAFS 200:2017). The ruminant shall enter the restrainer through the entrance gate. 159 The head of the ruminant shall be secured in the head gate (as applicable) and shall be 160 released after stunning. The testing agency shall make and record all measurements. 161 The stunned ruminant shall be removed from the restrainer through the discharge gate. 162 After each test trial, the area shall be cleaned and prepared for the next test trial. This 163 procedure shall be repeated for the succeeding test trials. 164

- 165 7.2 Test trial
- 166

167 There shall be at least two (2) test trials. Each test trial should have one (1) ruminant as 168 test animal.

- 169
- 170 **7.3 Data collection**
- 171

172 The record sheet for all the data and information during the test is given in Annex C. 173 Observations to be taken during the performance test shall be recorded in this sheet.

7.3.1 Noise level

7.3.1.1 The sound emitted by the machine, with and without load, shall be measured
using a sound level meter at the location of the operator or slaughterhouse personnel.
The noise level, expressed in decibel [dB (A)], shall be measured 50 mm away from the
ear level of the operator/s or slaughterhouse personnel.

7.3.1.2 The sound emitted by the machine without load shall be measured using a soundlevel meter at the location of the head gate.

7.3.1.3 For each data to be taken, there shall be a minimum of five (5) observations.
Before recording the data, it should be ensured that the operations and other functional
characteristics have been stabilized. The time of recording shall be properly spaced
during the whole duration of the test trial.

7.3.2 Pressure191

192 If applicable, the operating pressure, with and without load, shall be measured using a 193 pressure gauge.

194 8 Presentation of results

The restrainer specifications and the result of the tests shall be presented in tabular form
in which data shall be taken from Annexes B, C, and D. The observations made on the
restrainer while in operation shall be supported with photographs.

200 9 Test Report

202 The test report shall include the following information in the order given:

- **9.1** Name of Testing Agency;
- 206 9.2 Test Report Number;
- **9.3** Title; 209
- **9.4** Summary of Results;
- **9.5** Purpose and Scope of Test;
- **9.6** Methods of Test;
- **9.7** Description of the Machine;

9.8 Specifications;
9.9 Results;
9.10 Observations (include pictures); and
9.11 Name/s, Signature/s and Designation/s of Test engineer/s.

Minimum list of test instruments

Annex A

(informative)

	Items	Quantity		
A.1	Weighing scale Capacity: 700 kg	1		
A.2	Tape measure (at least 5m)	1		
A.3	Steel tape (at least 5m)	1		
A.4	Vernier caliper Accuracy: 0.05 mm Capacity: at least 200 mm	1		
A.6	Scientific calculator	1		
A.7	Sound level meter	1		
A.8	Pressure gauge Resolution: 0.1 bar Capacity: 15 bar	1		

234 235 236 237	Annex B (informative) Specifications of large ruminant restrainer		
238 239 240	Name of Test Applicant:		
240 241 242	Address:		
243 244	Tel. No.:		
245 246	Name of Manufacturer:		
247 248	Address:		
249 250 251	Tel. No.:		
251	General Information:		
253	Classification:	Maximum Weight Capacity:	
254	Serial No.:		
255		Test Engineer:	
256		Animal Welfare Inspector:	
257 258	Location of Test:	Date of Test:	

Items*	Manufacturer's specifications	Verification by the testing agency
B.1 Type	•	
B.2. Main frame		
B.2.1 Overall dimensions, mm		
B.2.1.1 Length		
B.2.1.2 Width		
B.2.1.3 Height		
B.2.2 Material		
B.3 Entrance gate		
B.3.1 Dimensions, mm		
B.3.1.1 Height		
B.3.1.2 Width		
B.3.2 Material		
B.3.3 Mode of attachment		
B.3.4 Features		
B.4 Counterweight		
B.4.1 Mass, kg		
B.4.2 Material		

Items*	Manufacturer's	Verification by the
	specifications	testing agency
B.5 Head gate		
B.5.1 Dimensions, mm		
B.5.1.1 Height		
B.5.1.2 Width		
B.5.2 Mode of attachment		
B.5.3 Material of main assembly		
B.5.4 Material of chin lift		
B.5.5 Features		
B.6 Discharge gate		
B.6.1 Dimensions, mm		
B.6.1.1 Length		
B.6.1.2 Height		
B.6.2 Material		
B.6.3 Mode of attachment		
B.6.4 Features		
B.7 Side wall		
B.7.1 Dimensions, mm		
B.7.1.1 Height		
B.7.1.2 Width		
B.7.2 Material		
B.8 Flooring		
B.8.1 Dimensions, mm		
B.8.1.1 Length		
B.8.1.2 Width		
B.8.2 Gap spacing, mm		
B.8.3 Material		
B.9 Rump pusher		
B.9.1 Type/Shape		
B.9.2 Dimensions, mm		
B.9.2.1 Length		
B.9.2.2 Width		
B.9.3 Material		
B.10 Discharge landing		
platform		
B.10.1 Length, m		
B.10.2 Width, m		
B.10.3 Gap spacing, mm		
B.10.4 Material		1
B.11 Cylinder/s		
B.11.1 Type (pneumatic/		
hydraulic)		
B.11.2 Bore, mm		


Items*	Manufacturer's specifications	Verification by the testing agency
B.11.3 Stroke, mm		
B.11.4 Operating pressure, Pa		
B.11.5 Features		
B.12 Pressure gauge		
B.12.1 Type		
B.12.2 Location		
B.13 Cable/Chain		
B.13.1 Material		
B.13.2 Size		

Annex C (informative) Performance Test Data Sheet

Test Trial No.	:	Date :	
Test Engineers	:	Location :	
Assistants	:	Machine :	
Test Applicant	:	Manufacturer:	

Items	Trial		Average
items	1	2	
C.1 Conditions of animal			
C.1.1 Animal			
C.1.2 Breed			
C.1.3 Girth, mm (refer to C.3)			
C.1.4 Weight, kg			
C.1.5 Length, mm (refer to C.3)			
C.2 Performance test			
C.2.1 Noise level, [dB(A)]			
C.2.1.1 Operator's ear level			
C.2.1.1.1 Without load			
C.2.1.1.2 With load			
C.2.1.2 Location of head gate, without load			
C.2.2 Capacity, kg			
C.2.3 Operating pressure (if available), Pa			
C.2.3.1 Without load			
C.2.3.2 With load			

C.3 Ruminant Body Measurement



C.4 Other Observations

C.4.1 Presence of safety features/locks

C.4.2 Accessibility of grease points

C.4.3 Sturdiness of the main frame

C.4.4 Sturdiness of the discharge gate

C.4.5 Sturdiness of the slider

C.4.6 Sturdiness of the head gate

C.4.7 Sturdiness of the rump pusher

C.4.8 Welded and/or bolted parts/joints before and after the test operation

C.4.9 Failure or abnormalities that may be observed on the restrainer or its component parts during and after the test operation

C.4.10 Number of operators

C.4.11 Vocalizations

C.4.12 Ruminant's body movements

C.4.13 Others

Bibliography

American Welding Society (AWS). (2000). *Structural welding code - Steel* (AWS D1.1: 2000)

https://www.academia.edu/10081213/AWS_D1_1_2000_Welding_Standard?emai I_work_card=view-paper

- Baumeister, T., E.A. Avallone and T. Baumeister III. (1978). *Marks' Standard Handbook for Mechanical Engineers*. 8th ed. McGraw-Hill, Inc. https://refacsmkn1crb.files.wordpress.com/2012/11/38102475-marks-standardhandbook-for-mechanical-engineers.pdf
- Grandin, T.G. (2005). *Recommended animal handling guidelines and audit guide for cattle, pigs and sheep* (2005 ed). American Meat Institute Foundation. <u>https://www.grandin.com/RecAnimalHandlingGuidelines.html</u>
- Grandin, T.G. (1993). *Teaching principles of behavior and equipment design for handling livestock.* Journal of Animal Science. (71), 1065- 1070. https://www.grandin.com/behaviour/principles/teach.html

Department of Agriculture (DA)

Bureau of Agriculture and Fisheries Standards (BAFS) Technical Working Group (TWG) for the Philippine National Standard (PNS) for Large Ruminant Restrainer – Specifications and Methods of Test

Chairperson

Aurelio Delos Reyes Jr.,Ph.D College of Engineering and Agro- Industrial Technology (CEAT) University of the Philippines Los Baños (UPLB)

Members

- 1 Engr. Mary Ann Evasco
- 2 Engr. Abbygail Jaylo
- 3 Engr. Maverick De Guzman DA-Bureau of Agricultural and Fisheries Engineering (BAFE)
- 4 Ronaldo Saludes, Ph.D CEAT – UPLB
- 5 Jovita Gonzales, Ph.D DA- Philippine Council for Agriculture and Fisheries (PCAF)

- 6 Annalyn Carreos Total Machinery and Trading
- 7 Engr. Marivic Crusada DA - National Meat Inspection Service (NMIS)
- 8 Eduardo Jose Manuel Jr., DVM DA- Bureau of Animal Industry (BAI)
- 9 Engr. Fatima Joy Raytana
 Engr. Ray Alipio
 UPLB Agricultural Machinery
 Testing and Evaluation Center
 (AMTEC)

BAFS Management Team

Karen Kristine Roscom Farlash Pancho Engr. Em Bentulan DA-BAFS

Advisers

Vivencio Mamaril, Ph.D / Myer Mula, Ph.D DA-BAFS



BUREAU OF AGRICULTURE AND FISHERIES STANDARDS

BPI Compound Visayas Avenue, Diliman, Quezon City 1101 Philippines T/ (632) 928-8741 to 64 loc. 3301-3319 E-mail: <u>bafs@da.gov.ph</u> Website: www.bafs.da.gov.ph